



Das Original

Oil stem seals dimension table

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Eling number
8	14	4	B NBR	322.415
8	14	4	A/B FPM	758.876
10	15	3	B OF NBR	010.804
10	18	6	A F NBR	011.304
10	20	4.5/7.5	B F WD FPM	599.255
12	24	6/5	A FPM	267.610
13	26	7	AS F NBR	281.514
14	24	7	B F NBR	037.109
15	21	5/7	AW/BS NBR	327.299
15	24	7	BD NBR	037.141
15	24	7	AS NBR	279.528
15	24	7	AS ACM	279.529
15	24	7	B F NBR	037.133
15	24	7	A RD ACM	089.613
15	32	7	AW RD PTFE/ACM	299.640
15	36.45/40	10.8	AAHU FPM	577.804
15	36.45/40	20.5	AAHU FPM	220.020
16	24	6	B VMQ	093.513
16	24	7	A NBR	044.008
16	30	15	AAJ NBR	829.463
17	28	7	A NBR	050.300
17	28	7	AS RD FPM	247.300
17	35	7	A NBR	054.003
18	27	5/8	AS OF NBR	244.082
18	30	7	AS F NBR	244.074
18	32	6	AS RD ACM	490.800
19.05	33.33	7.93	AS F NBR	278.556
20	30	7	A NBR	102.300
20	32	6	AS RD FPM	688.560
20	32	7	A F NBR	037.524
20	35	7/10	AW RD ACM	091.626
20	35	7	A NBR	106.208
20	35	7,5	ASW LD PTFE/ACM	789.950
20	42	7	AS F WD NBR	277.290
21	32	8	AS FPM	215.520
21	33	8/9	AS V NBR	007.544
21.9	40	8	ASW F RD ACM	244.040
22	32	7/8	AS NBR	075.175
22	32	7	AW ACM	528.190
22	32	7	A NBR	037.850
22	35	7/8	A NBR	120.103
22	35	7	AW F LD VMQ	092.614
22	45	7	ASW L LD FPM/ACM	508.608
22.2	40	12/17	AS RD ACM	043.605
23	35	7	A/BS RD FPM	440.710
23	36	6/7	A NBR	131.860

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
23	40	10/14	A RD ACM	089.575
24	39	8	ASW LD PTFE/AEM	242.620
24	50	8	ASW RD PTFE/ACM	505.600
25	32	5	B OF NBR	134.600
25	35	6	AS RD FPM	247.260
25	35	7/10	SP NBR	046.264
25	35	7	A NBR	135.208
25	35	7	AS NBR	038.075
25	35	7	A NBR	038.083
25	35	8	AD NBR	008.427
25	35	7	ASW LD FPM	174.200
25	37	7	A NBR	137.006
25	37	7	ASW RD FPM	174.210
25	38/49.7	10.5/15	ASW BD FPM	457.290
25	40	8	AS NBR	038.164
25	40	10	ASW F RD FPM	462.977
25	40	15	SP FPM	733.480
25	42	7	ASW F RD FPM	508.544
25	42	10	BS NBR	038.229
25	47	7	AS NBR	084.891
25	52	7	B NBR	038.385
25	62	10	AW/BS F FPM	763.772
25.5	37.5	6	AS RD FPM	332.480
26	37	7/8	AS V NBR	006.408
26	42	8/6	ASW RD FPM/ACM	755.141
26	42	8	AS F RD VMQ	049.557
26	42	10	AS F NBR	006.297
26	45	8	ASW WD FPM	339.280
26	45	10	B NBR	038.490
27	37	7	AW/BS RD FPM	069.540
27	42	8	AW/BS RD FPM	076.110
27	43	9	AW LD NBR	591.777
27	47	7	AS RD FPM	153.740
27	47	7	ASW RD PTFE/ACM	026.740
27.95	56	10	ASW RD ACM	050.560
28	38	7	ASW RD FPM	562.653
28	40	7	AW RD FPM	562.939
28	40	7	AW NBR	164.500
28	40	8/8.5	AS NBR	237.744
28	42	5	ASW RD FPM	073.890
28	42	6	ASW RD PTFE/ACM	584.880
28	42	7	ASW RD FPM	504.491
28	42	7	ASW F RD VMQ	546.968
28	42	8	AS LD ACM	012.180
28	47	8	ASW RD PTFE/ACM	159.714
28	47	10	B NBR	038.660
28	47	5.5	ASW RD FPM	169.370
28	49.85/61.5	16	SP RD NBR	038.709
29	45	8	AS LD VMQ	012.160
29	50	10	AW/BS F LD ACM	755.087
29.85	47	11.3	ASW RD ACM	128.240
29.9	47	8	AW F RD FPM/ACM	582.689
29.9	47	11.3	ASW RD PTFE/ACM	505.090

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
30	40	7/10	SP OF NBR	201.200
30	40	7	ASW F RD FPM	508.489
30	40	7	ASW RD PTFE/AEM	248.270
30	40	7	AS NBR	038.806
30	40	7	ASW RD FPM	598.993
30	40	7	A NBR	201.006
30	40	7	ASW RD PTFE/AEM	248.270
30	40	7	B NBR	038.814
30	40	7	ASW LD FPM	302.770
30	42	6	ASW RD FPM	365.940
30	42	7	ASW RD ACM	440.720
30	42	7	A NBR	203.408
30	42	7	ASW RD FPM	505.838
30	42	7	AS RD ACM	277.142
30	42	8	A LD ACM	302.430
30	42	8	AS RD FPM	598.760
30	42	8	AW WD ACM	203.808
30	42	8	AS LD FPM	598.770
30	43	8	AW/BS RD ACM	440.730
30	44	7	AS RD ACM	022.160
30	44	8	A/BS LD FPM	440.740
30	45	7	A/BS RD FPM	434.500
30	46	7	AS RD FPM	447.610
30	46	8	AS RD FPM	034.520
30	46	8	A/BS RD ACM	454.220
30	47	7	A F NBR	206.202
30	47	7	AS WD FPM	773.620
30	47	7	A WD FPM	135.150
30	47	7	A WD FPM	135.151
30	47	7	A RD FPM	753.866
30	47	7	ASW LD FPM/ACM	135.151
30	47	8	B NBR	038.873
30	47	8	AS NBR	206.806
30	47	10	A NBR	208.302
30	48	10	A RD ACM	038.938
30	50	7	ASW RD PTFE/ACM	026.770
30	50	10	AW F RD FPM/ACM	347.922
30	52	7	B F RD NBR	212.458
30	52	7	A NBR	308.919
30	52	7	AW/BS RD FPM	440.750
30	52	7	AW/BS RD ACM	332.220
30	52	9	C NBR	462.829
30	54	19	A LD FPM	393.880
31	41	7	AW/BS RD FPM	069.590
31	50	8	AW/BS F RD FPM	330.736
31	55	7	AW/BS RD FPM	688.580
31	52	8	AW WD ACM	469.120
31.5	42	7	A/BS RD FPM	056.900
32	42	6/7	AW/BS RD FPM	158.060
32	43	7	AW F LD FPM	906.400
32	44	6	ASW RD PTFE/FPM	169.620
32	44	6	ASW RD FPM	050.540
32	44	7	AW LD PTFE/ACM	906.630

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
32	44	8/9.5	ASW V NBR	007.552
32	45	6	AS RD FPM	583.050
32	45	7	A NBR	227.609
32	45	10	A LD ACM	303.291
32	46	6	AS RD ACM	777.471
32	46	7	A LD ACM	153.830
32	47	6	AS RD FPM	166.160
32	47	7	A NBR	228.206
32	47	7	ASW ACM	222.880
32	47	8	ASW RD PTFE/FPM	906.180
32	47	10	ASW RD PTFE/ACM	129.780
32	47	10	ASW F WD FPM/ACM	325.155
32	47	10	ASW LD PTFE/ACM	326.470
32	47	10	ASW OF LD FPM	798.040
32	47	10	AW RD PTFE/ACM	897.690
32	47	10	AW RD PTFE/ACM	897.690
32	48	7	AS RD FPM	576.320
32	50	10	ASW RD FPM	381.680
32	50	12	ASW BD RD FPM	381.681
32	52	7	A NBR	039.179
33	42	6	ASW RD PTFE/ACM	659.160
33	43	6	ASW F RD FPM	508.950
33	44	7	ASW F LD FPM	508.942
33	47	5	ASW RD FPM	023.590
33	50	10/12	BS F LD NBR	244.694
33	56	11.8	AW/B WD ACM	388.180
34	47	5.5	ASW RD FPM	331.530
34	48	7	AS RD VMQ	022.170
34	48	7	FPM AW/BS	355.700
34	48	8	AS RD VMQ	151.490
34	52	8	A NBR	048.364
34	60	10	A/BS FPM	375.470
34.9	54	8,5	ASW RD FPM	381.710
34.9	62	8	A/BS LD ACM	760.240
34.93	49.96	8	ASW F WD VMQ	586.757
35	46	7	AW/BS RD FPM	364.710
35	47	7	ASW RD PTFE/ACM	431.420
35	47	7	AS F RD VMQ	336.998
35	47	7	AW F RD FPM/ACM	504.483
35	47	7	A NBR	251.402
35	47	5.6	AS F RD FPM	336.999
35	48	7	ASW RD FPM	353.990
35	48	7	AW/BS F RD VMQ	702.269
35	48	10	ASW RD FPM	475.961
35	48	10	ASW F RD FPM/ACM	294.357
35	48	10	AW RD PTFE/ACM	377.450
35	48	10	ASW RD PTFE/ACM	155.560
35	49	6	AS RD ACM	010.360
35	50	7	ASW RD PTFE/ACM	374.680
35	50	7	ASW RD FPM	757.292
35	50	8/7	AW F RD FPM/ACM	694.658
35	50	8	ASW F RD FPM/ACM	507.806
35	50	8	AS LD VMQ	580.988

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
35	50	8	A F RD ACM	293.946
35	50	8	A F WD FPM	302.589
35	50	8	AS NBR	253.309
35	50	10	AS F RD VMQ	507.725
35	52	7	A NBR	048.380
35	52	10	A NBR	258.407
35	52	8	A NBR AS RD	353.060
35	54	10	ASW F RD ACM	095.222
35	54	15/10	AW/BS WD ACM	452.500
35	54.85	61.2	8.8	14.7
35	55	12/9	ASW RD ACM	587.044
35	62	7	ASW F WD ACM	580.202
35	62	10	A NBR	269.700
35	62	12	AS FPM	582.900
36	46	7	ASW RD PTFE/ACM	242.650
36	50	7	ASW F RD FPM/ACM	505.366
36	50	7	ASW LD PTFE/ACM	903.600
36	50	8	AS LD VMQ	151.480
36	50	8	AS RD FPM	583.030
36	50	8	ASW RD PTFE/ACM	505.100
36	50	7.5	AS LD FPM	691.640
36	50	7.5	AS RD ACM	261.460
36	54	7	AW/BS F RD FPM	763.691
36	54	7.5	A NBR	107.794
36	58	15	ASW F WD ACM	044.881
36	58	15	AS2W WD NBR	525.359
36	60	15	AS WD NBR	277.517
36.51	52.48	8	ASW F RD VMQ	586.730
37	50	6	AS RD VMQ	034.540
37	50	6	AS RD FPM	642.720
37	50	6	AS OF RD FPM	649.250
37	50	6	AS RD FPM	023.631
37	50	7.5	AS LD ACM	431.050
37	61	10/14	SP AW/B F RD ACM	586.994
37	61	10/14	A/BS RD ACM	268.420
37	78.3	8/12	SP AW/B F WD ACM	587.001
38	50	6	ASW RD FPM	135.140
38	50	6	AS RD FPM	694.300
38	50	7	ASW F WD FPM	586.668
38	50	8/7	AW/BS F RD FPM	763.918
38	52	6	ASW RD FPM	023.520
38	52	7	ASW ACM	175.890
38	52	7	ASW F RD FPM	525.871
38	52	7	A/BS F RD FPM	902.100
38	52	10	B NBR	039.780
38	54	7	AS RD ACM	817.295
38	55	7	ASW F RD FPM/ACM	311.940
39	50	7	ASW RD PTFE/ACM	655.190
39	50	7	ASW RD FPM	332.670
40	52	6	AS RD NBR	060.120
40	52	6	AS RD VMQ	151.510
40	52	7	BS NBR	039.926
40	52	7	A NBR	321.508

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
40	52	7	B NBR	039.918
40	52	7	A RD FPM	277.216
40	52	7	ASW ACM	221.970
40	52	7	AW/BS RD FPM	445.060
40	52	9	ASW F WD ACM	094.358
40	52/58	7.5	ASW F BD NBR	321.800
40	52/58	7.6	ASW F BD NBR	045.772
40	55	7	AW/BS RD FPM	290.710
40	55	7	A NBR	277.150
40	55	8	AS NBR	039.993
40	55	8	A/BS WD ACM	539.580
40	55	8	ASW F LD ACM	242.993
40	55	10	B NBR	044.318
40	55	10,2	A/BS WD ACM	539.581
40	55	6.4	ASW RD PTFE/FPM	026.750
40	55	6.5	AS RD FPM	076.220
40	56	7	B F RD VMQ	059.790
40	56	7	AW/B RD FPM	440.760
40	56	7	B RD ACM	325.007
40	58	10	A NBR	327.301
40	58	10	ASW WD FPM/ACM/PTFE	504.581
40	58	10	AS F NBR	102.946
40	58	10	ASW SP WD ACM	128.250
40	62	7	A NBR	108.448
40	62	7	ASW F LD FPM/ACM	509.957
40	62	8	ASW RD FPM	539.590
40	62	10	A NBR	330.809
40	62	10	A/BS RD FPM	172.630
40	62	12/16	B ACM	219.568
40	62	7.4	ASW RD PTFE/ACM	023.740
40	62	11.5	A NBR	040.142
40	70	11/18	A/BS2 RD FPM	456.980
40	70/76	11/13.5	SP RD ACM	152.940
40	70	11/15	A/B RD ACM	745.720
40	70	12/16	SP RD ACM	312.444
40	70	13/20	SP FPM/ACM	398.420
40	49.6	5.5/7.3	OF A VMQ	314.501
41	53	6	AS RD FPM	717.710
41	53	7	AS RD FPM	351.180
42	52	7.5	A/BS RD FPM	748.889
42	53	7	AS RD FPM	467.860
42	54	6	ASW RD FPM	157.200
42	55	7	AW/BS RD PTFE/ACM	655.340
42	55	7	AW F RD VMQ	225.614
42	55	7	ASW RD FPM/ACM	127.610
42	56	7	A NBR	344.400
42	56	7	ASW F RD FPM	757.497
42	56	6.5	ASW RD FPM/ACM	148.230
42	58	7	B F NBR	010.197
42	58	7	BS NBR	040.304
42	58	8	ASW RD FPM/ACM	290.760
42	58	11	ASW RD FPM	562.661
42	58/60	19/7	B F RD VMQ	249.173

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
42	60	6,8/10,5	AS RD FPM	695.040
42	60	7	AS RD FPM	473.150
42	60	8	ASW F RD ACM	767.921
42	60	10	A F NBR	040.320
42	62	8	A NBR	353.100
42	62	7	ASW F RD FPM/ACM	508.233
42	62	7	BS NBR	346.306
42	62	7	ASW RD PTFE/ACM	393.990
42	62	10	A F RD VMQ	597.023
42	62	10	A NBR	040.355
42	62	10	AS RD ACM	040.363
42	62	12	AW/BS F RD FPM	586.641
42	65	10	AW/BS RD FPM	071.550
42	65	12	BS F WD ACM	706.035
42	66	6	ASW F RD FPM/ACM	505.740
42	66	7	ASW RD PTFE/ACM	369.530
42.5	54.5	6	AS RD FPM	195.730
43	58	7	AW/B F RD FPM	466.042
43	59	10	ASW FPM	381.690
44	60	7	AS RD FPM	247.280
44	60	8	B F RD VMQ	319.104
44	60	10	AW/BS F RD FPM	761.796
44	60	10	AW/BS RD PTFE/ACM	214.680
44	67	10	ASW WD ACM	095.311
44.5	62	10	ASW F WD NBR	042.803
45	57	6.5	AS RD FPM	135.180
45	60	7	A NBR	040.606
45	60	8	ASW RD ACM	746.240
45	60	8	ASW F WD ACM	063.665
45	60	8	AW/BS RD FPM	718.600
45	60	8	ASW RD PTFE/AEM	248.300
45	60	9	AW/BS F RD ACM	590.762
45	60	10	A NBR	048.410
45	62	7	BS NBR	040.673
45	62	8	AS NBR	366.609
45	62	8	A/BS RD ACM	390.010
45	62/68	10/8	AS F BD NBR	044.369
45	62	10	A NBR	367.206
45	62	10	AW NBR	367.207
45	62	10	CS NBR	043.451
45	62	10	A/BS LD FPM	462.994
45	63	7	AS RD FPM	458.630
45	63	7.5	AS RD VMQ	266.340
45	64	12/7	SP F WD NBR	578.134
45	65	7	ASW RD FPM/ACM	362.730
45	65	9	BS F LA RD ACM	325.562
45	65	10/12	AS NBR	109.932
45	65	10	B NBR	040.843
45	65	10	A NBR	370.703
45	65	10	AW/BS F RD FPM	763.781
45	65	10	AS F RD ACM	216.046
45	65	11	A/B F WD ACM	705.838
45	65	9	A/BS WD ACM	521.470

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
45	67	8	ASW PTFE/ACM	424.841
45	67	8	ASW RD FPM	914.924
45	67	12/13	BS F LA RD FPM	305.529
45	67/72	12/13	ASW F RD FPM	284.785
45	67/72	12/13	ASW F BD RD FPM/ACM	287.202
45	68	10	AW WD ACM	089.567
45	68	10	A NBR	043.478
45	72	11	AW/BS F LD FPM	462.986
45	72	15	AS2W F WD NBR	277.525
45	74.5/79.5	12/3.6	ASW F BD RD FPM/ACM	312.010
45	75	8/11	ASW RD PTFE/ACM	359.260
45	75	10	A/BS LD FPM	338.920
45	75	13.5/20	SP RD PTFE/ACM	656.160
45	74.5	12/14.5	ASW BD RD ACM	284.742
45	74.5	12/13.7	ASW RD FPM/ACM	309.028
45	85.3	8/14	A/BS WD ACM	906.060
45	85.3	9.5/15.3	AW/B F WD ACM	587.915
45	85.3	10/18.5	AW F WD ACM	467.995
46	58	7	AS RD FPM	023.530
46	64	8	AW/BS F RD FPM	701.343
46	64	8	A/BS RD FPM	283.827
46	56.4	7	ASW RD FPM	542.030
47.5	62	7	ASW F LD FPM/ACM	503.754
47.6	66.8	11.1	ASW RD PTFE/ACM	516.406
47.62	63.5	9	A/BS RD FPM	023.640
48	58	4	A OF NBR	385.700
48	62	7	BS NBR	277.223
48	62	8	ASW FPM	582.890
48	62	8	AS RD FPM	227.620
48	63	6,5	AS RD FPM	261.090
48	64	12/6	BS F WD NBR	293.400
48	65	10	A NBR	388.904
48	65	10	AS RD PTFE/ACM	050.260
48	65	10	AS NBR	096.091
48	65	10	A/BS F RD FPM	586.676
48	65	10	B NBR	040.991
48	65	10	AW/BS OF RD FPM	735.260
48	65	12/8	B NBR	241,253
48	65	12	B NBR	460.915
48	68	9.3/6	A/BS WD NBR	366.230
48	68	10	ASW F RD FPM	749.885
48	69	10	B RD FPM	284.662
48	72	7/9	AS2 NBR	394.009
48	75	8	B F RD FPM	033.472
48	66.65	10	ASW F RD VMQ	330.965
48	68	8	AW/BS LD ACM	430.020
50	62	7	AS RD FPM	903.070
50	64	10/13	B NBR	411.701
50	65	8	A/BS WD ACM	454.260
50	65	8	A NBR	412.104
50	65	8	B F WD FPM	597.015
50	65	8	B NBR	041.114
50	65.2	10	ASW WD ACM	527.858

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
50	67.5	13.5/8	SP F NBR	464.872
50	68	8	ASW F RD FPM/ACM	508.470
50	68	10	A NBR	414.107
50	70	8	C NBR	108.642
50	70	10/13.5	A/BS F NBR	009.076
50	70	10	AW/BS RD FPM	419.660
50	70	11	AW RD PTFE/AEM	353.780
50	70	13.5/8	CS NBR	009.075
50	72	8	AW/BS RD PTFE/AEM	714.800
50	72	10	A NBR	418.501
50	80	14	SP RD FPM/ACM	431.110
50	80	11	SP RD PTFE/AEM	749.250
50.8	65	9.5	AS NBR	237.752
51	58	4	B OF NBR	222.940
51	65	7	ASW RD FPM	362.740
51	68	8	AW LD PTFE/ACM	068.140
51	68	7.5	AS RD FPM	431.040
51.5	64	6	AS RD FPM	381.050
52	68	8	ASW RD ACM	501.123
52	68	8	AW RD FPM	141.960
52	68	10	ASW F RD VMQ	465.194
52	68	13.5	BS NBR	763.152
52	70	8,5/14	AS RD FPM	562.350
52	72	12	BS NBR	091.901
52	72	12	BS F WD FPM	006.564
52	75	10/9	A/BS LD VMQ	893.587
53	71	11.5	BS WD NBR	151.920
53	68	7	AW/BS RD ACM	582.120
54	70	8	ASW LD FPM	703.550
54.8	70	9/9.6	AS F NBR	237.760
55	68	8	AW/BS RD FPM	477.010
55	68	8	AW/BS RD PTFE/ACM	301.890
55	68	8	AW/BS OF RD FPM	584.160
55	68	8.5	ASW NBR	349.844
55	68	8.5	ASW NBR	284.459
55	70	6/10.27	SP AS NBR	587.036
55	70	8	AW/BS RD FPM	419.730
55	70	8	A NBR	440.302
55	70	8	ASW RD PTFE/ACM	263.600
55	72	8	ASW RD PTFE/ACM	173.890
55	72	10	AW/BS RD FPM	818.364
55	75	8/13	A/BS F WD NBR	560.309
55	75	8/7	A/BS WD NBR	456.140
55	75	8/9.2	B RD ACM	515.340
55	75	8	ASW FPM	581.617
55	75	8	B F RD FPM	284.645
55	75	10	A/BS RD ACM	746.300
55	75	10	B NBR	041.335
55	75	10	ASW RD PTFE/ACM	733.130
55	75	12	C NBR	105.368
55	80	8	A/BS RD FPM	456.970
55	80	10	CS NBR	452.210
55	80	10	B NBR	446.602

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
55	80	10	A NBR	048.437
55	70.1	8/5.5	ASW F LD FPM/ACM	694.711
56	70	6	ASW RD FPM/ACM	394.110
56	72	8	AW/BS RD FPM	220.900
58	74	10	A LD FPM	092.170
58	75	12	C NBR	043.932
58	80	7	AS RD FPM	247.370
59	70,5	6	AS RD FPM	355.630
59	72	12/12.5	AW/BS F NBR	467.871
60	72	8	B NBR	460.702
60	73	11/7	A/BS FPM	016.620
60	74	8	A/BS WD ACM	454.820
60	75	7	ASW RD FPM/ACM	505.110
60	75	8	AS LD VMQ	725.770
60	75	8	ASW OF RD FPM	742.950
60	75	10	ASW FPM	344.480
60	78	7	AS LD ACM	431.060
60	80	8	A FPM	065.490
60	80	8	AS LD VMQ	166.180
60	80	8	A NBR	029.335
60	80	8	AS LD FPM	196.180
60	80	10/8.75	ASW WD ACM	495.890
60	80	10	AS NBR	041.491
60	85	10	AW RD FPM	557.846
60	90	10	A NBR	479.004
60	90	14/16.3	KS FPM	452.230
60.4	80	12	A/BS RD FPM	323.780
60.45	76.18	10	ASW F LD FPM	693.201
61	75	8	ASW RD PTFE/ACM	004.450
62	80/86	9/14	KS NBR	453.910
62	80	10	A/BS NBR	801.231
62	80	10/14.8	A/BS NBR	453.920
62	80	10/9.5	AW/BS NBR	801.230
62	80	10	C NBR	028.436
62	80	10	C NBR	484.300
62	80	12/11	ASW LD VMQ	352.136
63	76	8,8	AW/BS RD PTFE/ACM	901.260
63	80	12	BS ACM	563.382
64	80	8	AW/BS LD ACM	440.780
64	80	11.5/16	ASW NBR	008.592
64	80	13	AS NBR	008.591
64	88	6	ASW F RD FPM/ACM	509.949
64.9	90	10	AW/BS FPM	435.820
64.9	90	10	BS F LA RD FPM	587.958
65	54	7	A/BS RD FPM	763.692
65	79	10	ASW RD PTFE/ACM	902.860
65	79	20	ASW RD PTFE/ACM	257.400
65	80	8/5.2	B FPM	493.902
65	85	10	AW F LD VMQ	494.500
65	85	10	AW NBR	494.402
65	85	10	AS2W WD NBR	046.094
65	85	13/12.5	BS F LA RD FPM	033.457
65	85	15.5	A/BS2 WD FPM	451.120

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
65	90	13	AW/BS F RD FPM	553.272
65	90	13	BS NBR	041.866
65	90	15	B F RD VMQ	499.609
65	90	15	A/B F LA RD FPM	283.983
66	90	12	BS LA RD FPM	749.983
66	90	12	A/BS PTFE/ACM	061.680
66	90	16	SP RD PTFE/FPM	632.100
66.67	89.3	10	ASW RD FPM	919.994
68	85	10/9.5	AW/BS NBR	830.798
68	85	10	AW/B RD FPM	817.449
68	85	13	BS NBR	562.831
68	86	8	AS LD FPM	505.293
68	90	10/9.5	A/BS NBR	008.304
68	90	10/9.5	A/B F WD FPM	198.420
68	90	10	B F WD FPM	008.508
68	90	10	A NBR	251.720
68	90	13	BS F RD FPM	331.171
68	90	13	BS NBR	041.955
70	85	7	ASW RD FPM/ACM	542.060
70	85	8	AW/BS LD FPM	440.800
70	86	7	ASW LD PTFE/FPM	169.650
70	86	8	ASW LD FPM/ACM	050.550
70	88	8	A/BS LD FPM	440.810
70	90	10	B NBR	246.891
70	90	10	A F LD VMQ	513.326
70	90	10	AW F LD FPM/ACM	348.856
70	90	10	AW/BS RD FPM	763.144
70	90	10	A LD ACM	042.102
70	90	13.5/14.5	SP FPM	013.930
70	92	8.5	AS LD ACM	135.420
70	95	13/14.5	KS NBR	354.080
70	100	12	AW NBR	325.473
70	100	12.5/16	SP PTFE/ACM	477.680
70	79.5	5.3	BS OF NBR	222.000
70	81.5	6	AW OF V NBR	331.163
72	84/85.14	18	B F WD NBR	009.360
72	96	9	AS LD VMQ	034.530
72	105	13	BS NBR	008.559
72	105	13	C F WD FPM	008.745
72	105	19	SP FPM/NBR	023.330
72	98	8	ASW LD FPM	353.010
74	88	8	AW/BS LD FPM	069.600
74	89	8.5	AS LD FPM	458.620
74	90	10	AW/BS LD FPM	440.830
74	95	11	ASW RD FPM Vlies	084.791
75	90	11.5	SP ASW RD FPM/ACM	293.849
75	94	10	AS LD VMQ	817.287
75	95	10/9.5	A/BS FPM	451.140
75	95	10/9.5	A/BS NBR	104.320
75	95	10/9.5	A/B WD FPM	104.310
75	95	10/9.5	B F WD FPM	327.263
75	95	10	A NBR	528.102
75	95	10	AW F WD FPM/ACM	006.394

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
75	95	10	AW F LD FPM/ACM	326.798
75	95	12	A NBR	528.404
75	95	12	BS NBR	008.370
75	95	13	AW/BS NBR	562.866
75	95	13	C NBR	529.001
75	100	10/13	KS NBR	222.610
75	100	10	A NBR	531.308
75	100	10	A F NBR	530.107
75	100	11	AW/BS NBR	457.120
75	100	12/13	BS F RD FPM	525.316
75	107	8	ASW LD FPM	575.450
75	94.3	11.5	SP ACM	023.290
76	108	8	ASW LD FPM	318.360
76.2	125.39/134	16.5/19.4	KS NBR	454.010
76.2	101.68	12	A/BS F RD FPM	754.669
77	100.1	11.45	AW/BS F LD FPM	694.665
77	171.5	8.7	AS LD FPM	330.530
78	47	7	AW/BS LD FPM	034.347
78	100	9	ASW LD PTFE/FPM	428.970
78	100	12.7	AW/B RD VMQ Vlies	015.220
78	104	11	AW/BS RD PTFE/ACM	445.591
78	110	8,5	ASW LD FPM	286.230
78	135	12/21.5	SP FPM	221.710
79	99	9.6	AW/BS LD PTFE/ACM	375.560
79.33	95.25	11	AW/BS F LD FPM	763.713
79.33	95.28	11	ASW LD PTFE/FPM	550.680
80	95	8	A F NBR	043.737
80	96	8	AS LD FPM	247.290
80	98	10	A/BS F LD FPM	590.797
80	98	14.6	ASW LD PTFE/FPM	434.550
80	100	8	ASW F LD FPM/ACM	507.822
80	100	8	ASW LD VMQ	507.860
80	100	9	ASW OF LD FPM	007.750
80	100	9	ASW LD PTFE/ACM	745.740
80	100	10/9.5	A/B WD FPM	104.290
80	100	10/9.5	A/BS RD FPM	531.600
80	100	10	AS NBR	108.499
80	100	10	BS LA LD FPM	587.966
80	100	10	ASW LD VMQ	546.941
80	100	10	AW LD PTFE/ACM	762.229
80	100	10	A NBR	546.038
80	100	10	A/BS NBR	104.330
80	100	10	B NBR	804.940
80	100	10	AS NBR	104.331
80	100	10	ASW RD PTFE/ACM	382.100
80	100	11	ASW RD PTFE/ACM	592.970
80	100	12	BS NBR	008.354
80	100	12	B FPM	042.420
80	100	12	BS F RD LA RD FPM	527.823
80	100	13	BS NBR	042.463
80	100	13	A LD VMQ	128.210
80	104	3/10	SP OF FPM	175.910
80	135/154	12	BS LA RD FPM	379.300

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
80	150	12/20	SP F LA RD FPM	588.008
80	130.2	12/20	SP F LA RD FPM	588.016
81	100/137	10/15.5	SP WD FPM	265.960
81	104	11	AW/BS RD FPM/Vlies	084.920
81	100.1	11.45	AW/BS LD FPM	694.673
82	105	12	ASW F LD FPM	232.300
82.6	141.7/155	16.5/19.4	KS ACM	457.270
83	97	7	AS LD FPM	717.720
83	103	8	AS LD FPM	736.810
83	113	14	SP FPM/ACM	431.120
84	104	11	AS LD VMQ	151.500
84	117	7,5	ASW LD FPM	471.060
85	103	8	AS LD FPM	034.560
85	103	8	ASW LD FPM	449.290
85	105	6.8/11	ASW F LD FPM/ACM	711.720
85	105	8	ASW LD PTFE/ACM	369.470
85	105	8	ASW LD FPM/ACM	508.462
85	105	8	ASW OF LD FPM	331.330
85	105	9	ASW LD FPM/ACM	135.110
85	105	9	ASW LD FPM	258.280
85	105	10	B NBR	556.807
85	105	10	C NBR	109.673
85	105	10	B F LD FPM	033.464
85	105	11	ASW F LD FPM	342.093
85	105	11	ASW LD PTFE/AEM	158.430
85	105	11	ASW F LD FPM	829.056
85	105	12/18	KS RD FPM	222.630
85	105	12	ASW F LD FPM/ACM	315.494
85	105	12	AW/BS LD PTFE/ACM	728.880
85	105	12	B F NBR	033.480
85	105	13/9.5	A/BS NBR	198.430
85	105	13/9.5	A/B F WD FPM	198.440
85	105	13	BS NBR	096.067
85	105	13	B NBR	024.074
85	105	13	C NBR	557.005
85	105	13	B F WD FPM	008.680
85	105	8.8	ASW LD PTFE/FPM	026.790
85	105	8.8	ASW LD PTFE/ACM	000.220
85	110	12/17	A/BS FPM	504.560
85	110	13	AS NBR	300.896
85	145	12/37	SP FPM/NBR	447.080
85	145	12/32	SP FPM/NBR	065.510
85	155	12/33	SP FPM/NBR	220.660
85.7	114.3	13	AW/BS RD FPM	570.495
86	100	10	AS LD VMQ	247.380
86	103	10	AS LD FPM	707.340
86	104	11	ASW F LD FPM/ACM	581.879
86	105	5/6	AW F NBR	059.480
87	100	8	A LD FPM	060.110
88	108	10	ASW LD PTFE/ACM	374.590
88	108	11	ASW LD FPM	750.476
89	105	10	AS LD VMQ	457.130
89	106	8	AS LD FPM	261.110

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
89	109	10,3	AS LD VMQ	260.090
90	104	9	AW/BS OF LD FPM	492.060
90	104	11/9	ASW LD FPM/ACM	694.770
90	110	7	ASW F LD FPM/ACM	508.209
90	110	7	ASW LD PTFE/ACM	394.011
90	110	8	AW OF LD FPM	751.610
90	110	9/10.3	AS LD FPM	373.490
90	110	10	ASW F LD FPM/ACM	294.683
90	110	11	ASW RD PTFE/ACM	453.930
90	110	11	ASW F LD FPM/ACM	511.064
90	110	12	AW/BS LD FPM	569.030
90	110	12	A/BS LD PTFE/FPM	301.870
90	110	12	A/BS F LD FPM	702.994
90	110	12	ASW LD PTFE/ACM	257.770
90	110	12	ASW F LD FPM/ACM	311.898
90	110	12	ASW LD PTFE/ACM	284.930
90	110	13	A/BS NBR	567.779
90	110	13	ASW F FPM/ACM	514.950
90	110	15	BS F RD FPM	331.198
90	110	15	AW/BD FPM	762.830
90	115	13	ASW LD FPM	763.136
90	120	11	ASW RD PTFE/ACM	243.550
90	120	12/9.5	BS F RD FPM	919.462
90	120	13	C NBR	042.617
90	130	14	AW/CS2 WD FPM	022.550
90	145	10/15	A/BS RD FPM	435.180
90	145	10	A/BS LD FPM	435.340
90	151	10/15	A/BS RD FPM	435.990
90	112.7	13	C NBR	044.571
90	125.25	10	BS F LA RD FPM	587.991
92	109	8	AS LD FPM	778.330
92	110	7	ASW LD FPM	044.590
92	110	8,5	AS LD FPM	589.520
92	110	10	AW F LD VMQ	044.598
93	108	7	ASW F LD FPM/ACM	508.926
93	114/144	12/14.5	ASW LD PTFE/ACM	373.530
93	114	13	ASW LD FPM	914.932
93	114	11.5	ASW LD PTFE/ACM	524.215
93	117	12	BS F LA LD FPM	344.230
95	112	12.5	AW F LD FPM/ACM	294.098
95	115	13/12	BS F NBR	457.450
95	115	13	A/BS WD FPM	456.120
95	115	13	A/BS NBR	567.795
95	115	13	A/B LD FPM	141.950
95	115	15.5	A/BS2 LD FPM	222.830
95	118	13	KS LD FPM	454.060
95	120	12	AS RD ACM	042.676
95	120	13	BS LD FPM	071.570
95	120	13	CS NBR	108.723
95	120	13	C NBR	042.684
95	120	13	A/BS NBR	567.787
95	130	13/12	AW/BS F RD FPM	830.879
95	130	13	C NBR	042.714

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
95	130	16	KS FPM	454.000
95	116.5	11	ASW WD FPM	473.310
96	114	9	AW/BS OF LD FPM	742.960
98	110	7	A LD FPM	135.190
98	114	8	AS LD FPM	584.930
98	115	10	AS LD VMQ	266.350
98	120	7	ASW F LD FPM/ACM	509.930
98	142,5	9,5/14,6	AW LD PTFE/ACM	306.640
99	114	11	ASW LD FPM/ACM	294.060
100	118	10	AW/BS LD FPM	419.700
100	118	8.6	AS LD FPM	473.840
100	120	10	AW F LD FPM	052.530
100	120	11/16.5	KS NBR	477.860
100	120	13	C NBR	592.609
100	120	15	AW/BS F RD FPM	756.121
100	124	10.5/13.5	ASW F LD VMQ	247.189
100	124	12	ASW RD PTFE/ACM	493.330
100	124	13	AS LD FPM	829.226
100	124	13	AW/BS F LD FPM	762.172
100	125	12	AW/BS OF LD FPM	735.250
100	125	13	A/BS NBR	562.874
100	125	13	A/BS LD FPM	818.399
100	130	11	AW RD PTFE/ACM	369.901
100	130	12	B FPM	374.360
100	130	12	B NBR	519.243
100	130	12	A/B NBR	826.766
100	130	12	AW/BS RD PTFE/ACM	158.510
100	130	13	C NBR	042.773
100	130	13	AW/BS F NBR	814.172
100	130	14	KS VMQ	457.260
104	130	15/33	B NBR	044.636
105	120	8	BS F NBR	495.590
105	125	13	AW/BS LD ACM	746.310
105	130	11	BS RD FPM	288.039
105	130	12	AW F NBR	282.200
105	130	12	AW/BS RD PTFE/ACM	766.853
105	130	12	AW F LD FPM/ACM	314.994
105	130	12	AW/BS LD ACM	515.350
105	130	12	AW/BS F RD FPM	524.972
105	130	12	AW/BS F RD FPM	524.973
105	130	13	C NBR	042.846
105	130	15	AW/BS F LD FPM	756.148
106	125	8	ASW ACM	493.350
108	135	15	AW/BS RD FPM	714.500
110	130	12	ASW LD PTFE/ACM	503.208
110	130	12	ASW RD PTFE/ACM	306.760
110	130	13	ASW F LD FPM/ACM	298.247
110	130	13	BS LD LA FPM	323.772
110	130	14.5	AW/BS F LD VMQ	225.666
110	135	13	BS FPM	422.320
110	140	12/19	SP F WD FPM	522.911
110	140	12/21.5	SP F WD NBR	522.910
110	140	13	CS NBR	105.422

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
110	140	13	C NBR	612.103
110	133.3	12	C NBR	210.382
112	131/136.8	7.5/10.5	SP OF A NBR	586.781
112	147	13.65	KS FPM	381.260
114	135	13	AW/BS LD FPM	805.190
115	140	12	AW/BS LD PTFE/ACM	354.090
115	140	12	AW LD PTFE/ACM	310.050
115	140	12	AW FPM	454.090
115	140	12	AW/BS FPM	454.080
115	140	13/12	A/BS RD FPM	717.820
115	140	13/12	A/BS F NBR	562.882
115	140	13	C NBR	518.166
115	140	13	A NBR	019.364
115	140	13	AW/BS LD FPM	007.010
115	140	13	AW/B LD PTFE/ACM	445.600
115	140	16/12	BS F LA LD FPM	033.376
115	140	13.5	ASW LD FPM/ACM	033.377
115	140	15.5	AW/BS LD FPM	084.590
115	142	15.5	AW/BS RD FPM	084.330
115	150	13	C NBR	044.660
115	136.7	8/12	SP NBR	495.600
117.47	142.87	12.7	AW WD NBR	325.511
120	140	12	ASW RD PTFE/ACM	152.320
120	140	13	BS NBR	105.457
120	140	13	C NBR	042.935
120	140	13	BS F LD FPM	090.158
120	140	13	AW/BS F LD FPM	562.920
120	140	13	AW/BS LD PTFE/ACM	766.829
120	145	15/12	A/BS NBR	567.108
120	145	15	C NBR	044.679
120	150	14.3/20	KS NBR	220.450
120	150	15/12	A/BS NBR	457.710
120	150	15/20.2	A/BS NBR	383.260
120	150	15	CS NBR	010.901
120	150	15	C NBR	042.943
120	160	15/13	ASW WD NBR	081.570
121	170	15.5/17	KS FPM	452.280
125	142	13	ASVW WD NBR	292.650
125	143	13	ASW F WD NBR	817.252
125	150	12	AW/BS LD FPM	493.360
125	150	13	CS NBR	022.560
125	150	14	AW/CS FPM	451.100
125	150	15/13	A/BS F WD FPM	457.620
125	150	15/13	A/BS F WD NBR	210.294
125	160	18	BS F LD FPM	316.385
125	152.4	15	C NBR	044.687
127	150	12	A F LD VMQ	518.360
127	150	13/12	AW/BS F LD FPM	518.361
129	137,4	4,2	ACM	794.570
130	150	13	ASW LD FPM	084.610
130	155	12.5/16	SP PTFE/ACM	477.740
130	160	13	AW/BS LD PTFE/ACM	354.390
130	160	14	KS FPM	454.050

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
130	160	15	ASW F LD FPM	587.070
130	160	16	A/BS2 WD FPM	290.180
132	160	10	B FPM	485.890
133.3	155.6	14	B F WD NBR	522.856
133.3	158.71	12.4/14.6	ASW F LD FPM/ACM	587.842
134	161	16	ASW RD PTFE	278.000
135	153	13	AW/B RD PTFE/ACM	345.000
135	160	16/13	AW/BS F LD FPM	830.887
135	175	15.5/20	SP NBR	357.170
135	175	18	SP FPM/ACM	009.310
135	178	18	SP FPM/ACM	214.290
135	156.7	8/10.5	A/BS NBR	736.410
136	159	13	ASW RD PTFE/ACM	000.270
136	165	7.5/15.5	SP LD NBR	655.805
136	165	7.5/15.5	SP RD NBR	655.902
137	161.92	15/12	SP F WD NBR	586.803
139	164	12	ASW LD PTFE/ACM	250.760
139	170	11	BS LA FPM	517.130
139	170	11	AW/BS FPM	517.131
139	175	16.3	KS FPM	457.300
140	160	13	B NBR	255.637
140	160	13	C NBR	043.028
140	164	23.5	SP LA WD FPM	922.277
140	165	9.5/12	SP F WD FPM	477.140
140	165	12/15	AS2W F WD FPM/ACM	043.990
140	165	13/12	AW/BS LD FPM	121.860
142	170	15/16	KS NBR	222.620
145	167	13	ASW F WD NBR	817.260
145	170	15/20	SP F WD NBR	586.838
145	175	8	BS NBR	451.130
145	175/205	9/14	SP NBR	147.730
145	175	13	AW/B NBR	817.023
145	175	13	C FPM	033.146
145	175	13	ASW LD PTFE/ACM	090.510
145	175	13	C NBR	208.220
145	175	13	AW/B WD FPM	768.057
145	175	14	BS NBR	208.210
145	175	14	AW/BS NBR	768.065
145	175	15	AW/BS RD FPM	559.030
145	175	15	AW FPM	451.110
145	175	16	AW/BS2 F WD FPM	826.774
145	175	17	AW/BS WD FPM	022.850
145	175/205	18/20	SP FPM	147.731
145	185	13	ASW LD PTFE/ACM	904.820
148	168/170	32	B F WD NBR	522.864
150	172	13	ASW LD PTFE/ACM	457.220
150	172	18.3	AW LD VMQ	043.095
150	180	11/13	AS WD NBR	705.292
150	180	13	A NBR	109.657
150	180	15	AW/B LD PTFE/ACM	545.800
150	180	16/17.5	BS2 F WD FPM	590.738
150.81	177.8	12.7	A NBR	325.503
154	180	12	ASW LD PTFE/ACM	175.990

Shaft Diameter	Outer Diameter	Gauge	Materials/Types	Elring number
154	180	15	AW/BS F LD FPM	760.579
155	180	15	C NBR	204.730
155	180	15	AW/BS F LD FPM	760.315
155	180	15	ASW LD FPM	760.316
155	180	24/29	SP F WD FPM	598.925
158	188	14.5/18	KS BF NBR/FPM	919.888
160	180	10/11	BS NBR	008.672
160	180	10	A/B WD NBR	104.470
160	180	10	AW/BS NBR	104.480
160	180	10	B NBR	008.818
160	180	15	C NBR	671.908
160	190	13	ASW LD PTFE/ACM	233.530
160	190	15	AS NBR	306.096
165	190	13	B NBR	346.640
165	190	13	A NBR	675.407
166	191	16	ASW LD PTFE	278.020
168	188/190	30/32	BS F WD NBR	522.880
168	188/192.5	30	AS2 F WD FPM	693.162
170	190	8.5	A NBR	327.255
170	190	8.5	AS NBR	327.247
175	200	15	A NBR	103.986
179	200	15.5/16.5	KS FPM	456.130
180	200	12	BS NBR	348.376
180	200	12	BS FPM	018.670
180	200	17	CS WD FPM	453.990
180	205	15	AW/BS LD FPM	081.460
180	205	15	AW LD PTFE/ACM	453.851
185	210	13	A NBR	563.617
52,6	72	9	ASW RD PTFE/AEM	247.110
157,5	171,5	8	AS LD FPM	331.300
117,48	152,36	22	KS NBR	537.760